Fax: 0364-2521226 TEL: 0364-2521713



## GOVERNMENT OF INDIA CENTRAL WATER COMMISSION MEGHNA INVESTIGATION DIVISION MSHFCS Ltd BUILDING, 4<sup>TH</sup> FLOOR, NONGRIM HILLS SHILLONG-793003

**No.** MID/JEHQ-1/NIQ/2013/3075-78

## **NOTICE INVITING QUOTATION**

Dated: 26<sup>th</sup> September, 2014

Sealed quotations are hereby invited by the undersigned on behalf of the President of India for supply of following items as detailed below. **The quotations should reach in the office of the undersigned on or before 13-10-14 up to 15.00 hrs** and will be opened on the same day i.e **13-10-14 at 15.30 hrs** in the presence of quotationers or their authorized representatives, if any.

The undersigned reserves the right to accept or reject any or all the quotations without assigning any reason thereof.

1. STEVENSON SCREEN  Specifications  1. Standard width length between inner slats of louvers 315 mm height between middle of lower roof and floor 412 mm  Conditions & Requirements  • Double layered roof with ventilation provision.  • The screen shall comply with IS 5948 – 1970.  • All dimension requirements shall be met within 5% of specified dimension.  2. Supply of Pan Evaporimeter  5. Supply of Pan Evaporimeter  1. Pan size 1.22 x 0.255 m (diameter x height) accuracy of reading 0.1 mm pan evaporimeter copper sheet of thickness 1.0 ±0.1 mm point gauge and still well brass  2. Measuring cylinder material clean cast seamless acrylic plastic tubing or brass sheet bottom plate acrylic plastic sheet thermometer clamp brass platform rot resistant timber treated with creosote or other effective wood preservative inner diameter 122 mm graduation in cm.  Conditions & Requirements	Rate in Rs.)	Unit	Quantity	Description of Item	SN
Specifications 1. Standard width length between inner slats of louvers 315 mm height between middle of lower roof and floor 412 mm  Conditions & Requirements  • Double layered roof with ventilation provision. • The screen shall comply with IS 5948 – 1970. • All dimension requirements shall be met within 5% of specified dimension.  Supply of Pan Evaporimeter  05 nos.  Specification 1. Pan size 1.22 × 0.255 m (diameter × height) accuracy of reading 0.1 mm pan evaporimeter copper sheet of thickness 1.0 ±0.1 mm point gauge and still well brass  2. Measuring cylinder material clean cast seamless acrylic plastic tubing or brass sheet bottom plate acrylic plastic sheet thermometer clamp brass platform rot resistant timber treated with creosote or other effective wood preservative inner diameter 122 mm graduation in cm.		Noc	O.F.	STEVENSON SCREEN	1.
1. Standard width length between inner slats of louvers 560 mm width between inner slats of louvers 315 mm height between middle of lower roof and floor 412 mm  Conditions & Requirements  • Double layered roof with ventilation provision. • The screen shall comply with IS 5948 – 1970. • All dimension requirements shall be met within 5% of specified dimension.  2. Supply of Pan Evaporimeter  05 nos.  Specification 1. Pan size 1.22 x 0.255 m (diameter x height) accuracy of reading 0.1 mm pan evaporimeter copper sheet of thickness 1.0 ±0.1 mm point gauge and still well brass  2. Measuring cylinder material clean cast seamless acrylic plastic tubing or brass sheet bottom plate acrylic plastic sheet thermometer clamp brass platform rot resistant timber treated with creosote or other effective wood preservative inner diameter 122 mm graduation in cm.		NOS.	05	Specifications	
width between inner slats of louvers 315 mm height between middle of lower roof and floor 412 mm  Conditions & Requirements Double layered roof with ventilation provision. The screen shall comply with IS 5948 – 1970. All dimension requirements shall be met within 5% of specified dimension.  Supply of Pan Evaporimeter  Specification 1. Pan size 1.22 x 0.255 m (diameter x height) accuracy of reading 0.1 mm pan evaporimeter copper sheet of thickness 1.0 ±0.1 mm point gauge and still well brass  C. Measuring cylinder material clean cast seamless acrylic plastic tubing or brass sheet bottom plate acrylic plastic sheet thermometer clamp brass platform rot resistant timber treated with creosote or other effective wood preservative inner diameter 122 mm graduation in cm.					
height between middle of lower roof and floor 412 mm  Conditions & Requirements Double layered roof with ventilation provision. The screen shall comply with IS 5948 – 1970. All dimension requirements shall be met within 5% of specified dimension.  Supply of Pan Evaporimeter  Supply of Pan Evaporimeter  05 nos.  Specification 1. Pan size 1.22 x 0.255 m (diameter x height) accuracy of reading 0.1 mm pan evaporimeter copper sheet of thickness 1.0 ±0.1 mm point gauge and still well brass  C. Measuring cylinder material clean cast seamless acrylic plastic tubing or brass sheet bottom plate acrylic plastic sheet thermometer clamp brass platform rot resistant timber treated with creosote or other effective wood preservative inner diameter 122 mm graduation in cm.				length between inner slats of louvers 560 mm	
Conditions & Requirements  Double layered roof with ventilation provision. The screen shall comply with IS 5948 – 1970. All dimension requirements shall be met within 5% of specified dimension.  Supply of Pan Evaporimeter  Specification 1. Pan size 1.22 x 0.255 m (diameter x height) accuracy of reading 0.1 mm pan evaporimeter copper sheet of thickness 1.0 ±0.1 mm point gauge and still well brass  C. Measuring cylinder material clean cast seamless acrylic plastic tubing or brass sheet bottom plate acrylic plastic sheet thermometer clamp brass platform rot resistant timber treated with creosote or other effective wood preservative inner diameter 122 mm graduation in cm.					
Conditions & Requirements  • Double layered roof with ventilation provision. • The screen shall comply with IS 5948 – 1970. • All dimension requirements shall be met within 5% of specified dimension.  2. Supply of Pan Evaporimeter  5. Specification 1. Pan 5. Size 1.22 x 0.255 m (diameter x height) 5. accuracy of reading 0.1 mm 5. pan evaporimeter copper sheet of thickness 1.0 ±0.1 mm point gauge and still well brass  2. Measuring cylinder 5. material clean cast seamless acrylic plastic tubing or brass sheet 5. bottom plate acrylic plastic sheet 5. thermometer clamp brass 5. platform rot resistant timber treated with creosote or other effective wood preservative inner diameter 122 mm 6. graduation in cm.					
Double layered roof with ventilation provision. The screen shall comply with IS 5948 – 1970. All dimension requirements shall be met within 5% of specified dimension.  Supply of Pan Evaporimeter  Specification 1. Pan size 1.22 x 0.255 m (diameter x height) accuracy of reading 0.1 mm pan evaporimeter copper sheet of thickness 1.0 ±0.1 mm point gauge and still well brass  C. Measuring cylinder material clean cast seamless acrylic plastic tubing or brass sheet bottom plate acrylic plastic sheet thermometer clamp brass platform rot resistant timber treated with creosote or other effective wood preservative inner diameter 122 mm graduation in cm.				412 mm	
The screen shall comply with IS 5948 – 1970. All dimension requirements shall be met within 5% of specified dimension.  Supply of Pan Evaporimeter  Specification 1. Pan size 1.22 x 0.255 m (diameter x height) accuracy of reading 0.1 mm pan evaporimeter copper sheet of thickness 1.0 ±0.1 mm point gauge and still well brass  C. Measuring cylinder material clean cast seamless acrylic plastic tubing or brass sheet bottom plate acrylic plastic sheet thermometer clamp brass platform rot resistant timber treated with creosote or other effective wood preservative inner diameter 122 mm graduation in cm.				Conditions & Requirements	
• All dimension requirements shall be met within 5% of specified dimension.  2. Supply of Pan Evaporimeter  5. Specification  1. Pan  5. Size 1.22 x 0.255 m (diameter x height)  5. Accuracy of reading 0.1 mm  5. pan evaporimeter copper sheet of thickness 1.0 ±0.1  5. Measuring cylinder  6. Measur					
5% of specified dimension.  2. Supply of Pan Evaporimeter  Specification 1. Pan size 1.22 x 0.255 m (diameter x height) accuracy of reading 0.1 mm pan evaporimeter copper sheet of thickness 1.0 ±0.1 mm point gauge and still well brass  2. Measuring cylinder material clean cast seamless acrylic plastic tubing or brass sheet bottom plate acrylic plastic sheet thermometer clamp brass platform rot resistant timber treated with creosote or other effective wood preservative inner diameter 122 mm graduation in cm.				• •	
2. Supply of Pan Evaporimeter  Specification 1. Pan size 1.22 x 0.255 m (diameter x height) accuracy of reading 0.1 mm pan evaporimeter copper sheet of thickness 1.0 ±0.1 mm point gauge and still well brass  2. Measuring cylinder material clean cast seamless acrylic plastic tubing or brass sheet bottom plate acrylic plastic sheet thermometer clamp brass platform rot resistant timber treated with creosote or other effective wood preservative inner diameter 122 mm graduation in cm.				·	
Specification 1. Pan size 1.22 x 0.255 m (diameter x height) accuracy of reading 0.1 mm pan evaporimeter copper sheet of thickness 1.0 ±0.1 mm point gauge and still well brass  2. Measuring cylinder material clean cast seamless acrylic plastic tubing or brass sheet bottom plate acrylic plastic sheet thermometer clamp brass platform rot resistant timber treated with creosote or other effective wood preservative inner diameter 122 mm graduation in cm.		noc	O.E.		າ
size 1.22 x 0.255 m (diameter x height) accuracy of reading 0.1 mm pan evaporimeter copper sheet of thickness 1.0 ±0.1 mm point gauge and still well brass  2. Measuring cylinder material clean cast seamless acrylic plastic tubing or brass sheet bottom plate acrylic plastic sheet thermometer clamp brass platform rot resistant timber treated with creosote or other effective wood preservative inner diameter 122 mm graduation in cm.		1105.	05	Supply of Pail Evaporimeter	۷.
size 1.22 x 0.255 m (diameter x height) accuracy of reading 0.1 mm pan evaporimeter copper sheet of thickness 1.0 ±0.1 mm point gauge and still well brass  2. Measuring cylinder material clean cast seamless acrylic plastic tubing or brass sheet bottom plate acrylic plastic sheet thermometer clamp brass platform rot resistant timber treated with creosote or other effective wood preservative inner diameter 122 mm graduation in cm.					
accuracy of reading 0.1 mm pan evaporimeter copper sheet of thickness 1.0 ±0.1 mm point gauge and still well brass  2. Measuring cylinder material clean cast seamless acrylic plastic tubing or brass sheet bottom plate acrylic plastic sheet thermometer clamp brass platform rot resistant timber treated with creosote or other effective wood preservative inner diameter 122 mm graduation in cm.					
pan evaporimeter copper sheet of thickness 1.0 ±0.1 mm point gauge and still well brass  2. Measuring cylinder material clean cast seamless acrylic plastic tubing or brass sheet bottom plate acrylic plastic sheet thermometer clamp brass platform rot resistant timber treated with creosote or other effective wood preservative inner diameter 122 mm graduation in cm.					
2. Measuring cylinder material clean cast seamless acrylic plastic tubing or brass sheet bottom plate acrylic plastic sheet thermometer clamp brass platform rot resistant timber treated with creosote or other effective wood preservative inner diameter 122 mm graduation in cm.					
material clean cast seamless acrylic plastic tubing or brass sheet bottom plate acrylic plastic sheet thermometer clamp brass platform rot resistant timber treated with creosote or other effective wood preservative inner diameter 122 mm graduation in cm.					
or brass sheet bottom plate acrylic plastic sheet thermometer clamp brass platform rot resistant timber treated with creosote or other effective wood preservative inner diameter 122 mm graduation in cm.				2. Measuring cylinder	
bottom plate acrylic plastic sheet thermometer clamp brass platform rot resistant timber treated with creosote or other effective wood preservative inner diameter 122 mm graduation in cm.				in the second se	
thermometer clamp brass platform rot resistant timber treated with creosote or other effective wood preservative inner diameter 122 mm graduation in cm.				1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	
platform rot resistant timber treated with creosote or other effective wood preservative inner diameter 122 mm graduation in cm.					
inner diameter 122 mm graduation in cm.				platform rot resistant timber treated with creosote or	
graduation in cm.					
Conditions & Requirements				gradation in ciri.	
• The pan shall comply with IS 5973 - 1970.				• The pan shall comply with IS 5973 - 1970.	

3.	Thermometers:	05	nos.	
	<ol> <li>Specifications:</li> <li>Maximum Thermometers: Mercury-in-glass, having a range from -35°C to +55°C.</li> <li>Minimum Thermometers: Alcohol-in-glass, having a range from -40°C to +50°C.</li> <li>Ordinary Thermometer (Wet &amp; Dry Bulb):</li> </ol>		(each)	
	Mercury-in-glass, having a range from -35°C to +55°C.  The graduation intervals for all the thermometers should be 0.5°C. The accuracy of ordinary thermometers and maximum thermometers should be ±0.2°C and for minimum thermometers it should be ±0.3°C.			

## **Terms & Conditions:**

- 1. The quotations duly signed should be properly sealed and either dropped in quotation Box in the office of the Executive Engineer, Meghna Investigation Division, MSHFCS Ltd. Building, 4<sup>th</sup> Floor, Nongrim Hills, Shillong-793003 or send by post. The sealed envelope should be superscribed "Quotation for Meteorological Instruments-II due on 13-10-14".
- 2. In the event of the date of opening of quotation being a holiday, quotations will be opened on the next working day with timings unchanged.
- 3. Quotationers must have PAN/TIN/Service Tax number/VAT.
- 4. Photocopies of Authorized Dealership Certificate from manufacturer should be enclosed along with the quotations.
- 5. The pamphlets / brochures should be submitted along with the quotation.
- 6. The undersigned does not bind himself to accept the lowest quotation and reserve the right to accept or reject any or all the quotations without assigning any reason thereof.
- 7. The material must be IMD certified.
- 8. The material must be of standard quality and as per specifications and free from all defects. The material if found defective subsequently or not conforming to the specifications as stated above, have to be replaced by the firm without any additional charges.
- 9. The material shall have a warranty of minimum one year from the date of supply or as provided by the manufacturer, whichever is higher.
- 10. Material should be delivered at office of the Executive Engineer, Meghna Investigation Division, MSHFCS Ltd. Building, 4<sup>th</sup> Floor, Nongrim Hills, Shillong-793003, Meghalava, only.
- 11. The quantity of materials may be increased or decreased at the time of supply order.
- 12. Material should be supplied within 30 days from the date of supply order.
- 13. The rates should be F.O.R. destination at Office of Executive Engineer, Meghna Investigation Division, MSHFCS Ltd. Building, 4<sup>th</sup> Floor, Nongrim Hills, Shillong-793003, Meghalaya, and inclusive of all taxes/charges including VAT/Service Tax/Transport charges/insurance etc.
- 14. Rates quoted should be valid at least for 90 days from the date of opening.
- 15. The rate should be quoted both in words and figure.
- 16. The payment will be made by account payee cheque for local supplier or by Demand Draft for outstation supplier on production of pre-receipted bill in triplicate only after satisfactory supply of the materials in good condition and as per specification.
- 17. TDS shall be deducted from the bill at the time of payment as per latest Govt. orders.

18. Security deposit @ of 10% of the total amount will be deducted from the bill amount and the same will be released after 60 days beyond the completion of warranty period.

Sd/-Executive Engineer MID, CWC, Shillong

## Copy to:

- 1. The The Superintending Engineer, Meghna Circle, Central Water Commission, Silchar (Assam).
- 2. Accounts Branch, Meghna Investigation Division.
- 3. DB, Meghna Investigation Division.
- 4. Notice board of office of Executive Engineer, Meghna Investigation Division.