भारत सरकार जल शक्ति मंत्रालय जल संसाधन, नदी विकास एवं गंगा संरक्षण विभाग केंद्रीय जल आयोग उत्तर पूर्वी अन्वेषण मण्डल-॥



Government of India
Ministry of Jal Shakti
Dept. of Water Resources, RD&GR
Central Water Commission
North East Investigation Division-II

Date: 20.02.2024

NEID-II/HQ/NIQ/2023-24/22b - 27

NOTICE INVITING QUOTATION

For and on behalf of the President of India, sealed quotations are invited by the undersigned from the authorized / reputed contractor/firms for the work of "Repair and Maintenance of quarter E-3 and E-7 under NEID-II, CWC, Aizawl" The Sealed Quotation will be received in the office of undersigned i.e. O/o Executive Engineer, NEID-II, CWC, Aizawl during working hours up to 13:00 hrs. On or before 26/02/2024 & shall be opened on same day by 15:30 hrs. by the undersigned/authorized official in presence of interested quotations or their authorized representatives who desired to remain present at the time of opening of quotations.

Description of the work.	Estimate cost	Last date & time for receiving quotation.	Date & time for opening quotation	Location
Repair and Maintenance of Quarter-E-3 and E-7 at NEID-II, CWC, AIZAWL	1,79,282.00/-	26/02/2024 13:00	26/02/2024 15:30	NEID-II, CWC, Aizawl

(Nishant Kumar) Executive Engineer NEID-II, CWC, Aizawl

Copy along with copies of quotation for information and wide circulation to:

- 1. The Accounts Branch, NEID-II, CWC, Aizawl.
- 2. Notice Board.

LimitedTenderForm/Quotation

NameoftheProcuringEntityCentral Water Commission

Firm's Reference	2	Date	
FirmRegistrationNo.(ifany)		PAN (attach photocopy)	
TIN/VAT/GSTNo.		Address:office of the Executi	ive Engineer North
Phone	LIMITED TENDER	Eastern Investigation Divisio Commission, Aizawl.	
Fax	FORM	, , , , , , , , , , , , , , , , , , , ,	
Email	1		
M/s:	EnquiryNo.andD ate	NEID-II/HQ/NIQ/2023-24/	
	Date of Tender Opening	20.02.2024	
	The tender would openingabove, att	ate of tender	

Please submit on or before 13:00 hrs. on the date of tender opening, your quotation for the followingworks, in accordance with the terms and conditions printed overleaf, in a sealed cover, marked on top with—Enquiry No: Date of Tender Opening.

Yours Sincerely

Sd/-

Designation with office TenderSchedule: AllRatesinFiguresandinWordsinRupees

SI. No	DescriptionandSpecification	Qty.	Unit	Performa nce terms	RateperUnit	Taxes &Duti es	Packin g/forwa rding/ If any	Total Amount
1	Repair and Maintenance of Quarter-E-3 and E-7 at NEID-II, CWC, AIZAWL. Dismantling doors, windows and clerestory windows (steel or wood) shutter including chowkhats, architrave, holdfasts etc. complete and stacking within 50 metres lead: 15.12.1 Of area 3 sq. metres and below Quarter-E-3 and E-7	3.0	Each	As per SOP of work and in accordance with the direction given by Engineer-in- charge				
2	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level 1:3:6 (1 Cement : 3 coarse sand (zone-III) derived from natural sources : 6 graded stone aggregate 40 mm nominal size derived from natural sources Quarter-E-3 and E-7	0.264	Cum	-do-				
3	Providing and fixing Ist quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours,	18.30	Sqm	-do-			,	

	shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge, in skirting, risers of steps and dados, over 12 mm thick bed of cement mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm, including pointing in white cement mixed with pigment of matching shade complete. Quarter-E-3 and E-7					
4	Providing and fixing 1st quality ceramic glazed floor tiles conforming to IS: 15622 (thickness to be specified by the manufacturer) of approved make in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-Charge in skirting, risers of steps and dados over 12 mm thick bed of cement Mortar 1:3 (1 cement: 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm including pointing in white cement mixed with pigment of matching shade complete. Quarter-E-3 and E-7	5.28	Sqm	-do-		
5	Providing and fixing panelling or panelling and glazing in panelled or panelled and glazed shutters for doors, windows and clerestory windows (Area of opening for panel inserts excluding portion inside grooves or rebates to be measured). Panelling for panelled or panelled and glazed shutters 25 mm to 40 mm thick: Second class teak wood Quarter-E-3 and E-7	8.80	Sqm	-do-		
6	Providing and fixing factory made uPVC door frame made of uPVC extruded sections having an overall dimension as below (tolerance ±1mm), with wall thickness 2.0 mm (± 0.2 mm), corners of the door frame to be Jointed with galvanized brackets and stainless steel screws, joints mitred and Plastic welded. The hinge side vertical of the frames reinforced by galvanized M.S. tube of size 19 X 19 mm and 1mm (± 0.1 mm) wall thickness and 3 nos. stainless steel hinges fixed to the frame complete as per manufacturer's specification and direction of Engineer incharg:Extruded section profile size 48x40 mm		Rm	-do-		

*

Quarter-E-3 and E-7 Providing and fixing factory made panel PVC door shutter consisting of frame made out of M.S. tubes of 19 gauge thickness and size of 19 mm x 19 mm for styles and 15x15 mm for top & bottom rails. M.S. frame on inner side, and joined together with solvent cement adhesive. An additional 5 mm thick PVC strip of 20 mm width is to be stuck on the interior side of the 'C' Channel using PVC solvent adhesive etc. complete shall have a coat of steel primers of approved make and manufacture. M.S. frame covered with 5 mm thick heat moulded PVC 'C' channel of size 30 mm thickness, 70 mm width out of which 50 mm shall be flat and 20 mm shall be tapered in 45 degree angle on both side forming styles and 5 mm thick, 95 mm wide PVC sheet out of which 75mm shall be flat and 20 mm shall be tapered in	
panel PVC door shutter consisting of frame made out of M.S. tubes of 19 gauge thickness and size of 19 mm x 19 mm for styles and 15x15 mm for top & bottom rails. M.S. frame on inner side, and joined together with solvent cement adhesive. An additional 5 mm thick PVC strip of 20 mm width is to be stuck on the interior side of the 'C' Channel using PVC solvent adhesive etc. complete shall have a coat of steel primers of approved make and manufacture. M.S. frame covered with 5 mm thick heat moulded PVC 'C' channel of size 30 mm thickness, 70 mm width out of which 50 mm shall be flat and 20 mm shall be tapered in 45 degree angle on both side forming styles and 5 mm thick, 95 mm wide PVC sheet out of which 75mm shall be	
of frame made out of M.S. tubes of 19 gauge thickness and size of 19 mm x 19 mm for styles and 15x15 mm for top & bottom rails. M.S. frame on inner side, and joined together with solvent cement adhesive. An additional 5 mm thick PVC strip of 20 mm width is to be stuck on the interior side of the 'C' Channel using PVC solvent adhesive etc. complete shall have a coat of steel primers of approved make and manufacture. M.S. frame covered with 5 mm thick heat moulded PVC 'C' channel of size 30 mm thickness, 70 mm width out of which 50 mm shall be flat and 20 mm shall be tapered in 45 degree angle on both side forming styles and 5 mm thick, 95 mm wide PVC sheet out of which 75mm shall be	
19 gauge thickness and size of 19 mm x 19 mm for styles and 15x15 mm for top & bottom rails. M.S. frame on inner side, and joined together with solvent cement adhesive. An additional 5 mm thick PVC strip of 20 mm width is to be stuck on the interior side of the 'C' Channel using PVC solvent adhesive etc. complete shall have a coat of steel primers of approved make and manufacture. M.S. frame covered with 5 mm thick heat moulded PVC 'C' channel of size 30 mm thickness, 70 mm width out of which 50 mm shall be flat and 20 mm shall be tapered in 45 degree angle on both side forming styles and 5 mm thick, 95 mm wide PVC sheet out of which 75mm shall be	
mm x 19 mm for styles and 15x15 mm for top & bottom rails. M.S. frame on inner side, and joined together with solvent cement adhesive. An additional 5 mm thick PVC strip of 20 mm width is to be stuck on the interior side of the 'C' Channel using PVC solvent adhesive etc. complete shall have a coat of steel primers of approved make and manufacture. M.S. frame covered with 5 mm thick heat moulded PVC 'C' channel of size 30 mm thickness, 70 mm width out of which 50 mm shall be flat and 20 mm shall be tapered in 45 degree angle on both side forming styles and 5 mm thick, 95 mm wide PVC sheet out of which 75mm shall be	
mm for top & bottom rails. M.S. frame on inner side, and joined together with solvent cement adhesive. An additional 5 mm thick PVC strip of 20 mm width is to be stuck on the interior side of the 'C' Channel using PVC solvent adhesive etc. complete shall have a coat of steel primers of approved make and manufacture. M.S. frame covered with 5 mm thick heat moulded PVC 'C' channel of size 30 mm thickness, 70 mm width out of which 50 mm shall be flat and 20 mm shall be tapered in 45 degree angle on both side forming styles and 5 mm thick, 95 mm wide PVC sheet out of which 75mm shall be	
frame on inner side, and joined together with solvent cement adhesive. An additional 5 mm thick PVC strip of 20 mm width is to be stuck on the interior side of the 'C' Channel using PVC solvent adhesive etc. complete shall have a coat of steel primers of approved make and manufacture. M.S. frame covered with 5 mm thick heat moulded PVC 'C' channel of size 30 mm thickness, 70 mm width out of which 50 mm shall be flat and 20 mm shall be tapered in 45 degree angle on both side forming styles and 5 mm thick, 95 mm wide PVC sheet out of which 75mm shall be	
together with solvent cement adhesive. An additional 5 mm thick PVC strip of 20 mm width is to be stuck on the interior side of the 'C' Channel using PVC solvent adhesive etc. complete shall have a coat of steel primers of approved make and manufacture. M.S. frame covered with 5 mm thick heat moulded PVC 'C' channel of size 30 mm thickness, 70 mm width out of which 50 mm shall be flat and 20 mm shall be tapered in 45 degree angle on both side forming styles and 5 mm thick, 95 mm wide PVC sheet out of which 75mm shall be	
adhesive. An additional 5 mm thick PVC strip of 20 mm width is to be stuck on the interior side of the 'C' Channel using PVC solvent adhesive etc. complete shall have a coat of steel primers of approved make and manufacture. M.S. frame covered with 5 mm thick heat moulded PVC 'C' channel of size 30 mm thickness, 70 mm width out of which 50 mm shall be flat and 20 mm shall be tapered in 45 degree angle on both side forming styles and 5 mm thick, 95 mm wide PVC sheet out of which 75mm shall be	
PVC strip of 20 mm width is to be stuck on the interior side of the 'C' Channel using PVC solvent adhesive etc. complete shall have a coat of steel primers of approved make and manufacture. M.S. frame covered with 5 mm thick heat moulded PVC 'C' channel of size 30 mm thickness, 70 mm width out of which 50 mm shall be flat and 20 mm shall be tapered in 45 degree angle on both side forming styles and 5 mm thick, 95 mm wide PVC sheet out of which 75mm shall be	
stuck on the interior side of the 'C' Channel using PVC solvent adhesive etc. complete shall have a coat of steel primers of approved make and manufacture. M.S. frame covered with 5 mm thick heat moulded PVC 'C' channel of size 30 mm thickness, 70 mm width out of which 50 mm shall be flat and 20 mm shall be tapered in 45 degree angle on both side forming styles and 5 mm thick, 95 mm wide PVC sheet out of which 75mm shall be	
Channel using PVC solvent adhesive etc. complete shall have a coat of steel primers of approved make and manufacture. M.S. frame covered with 5 mm thick heat moulded PVC 'C' channel of size 30 mm thickness, 70 mm width out of which 50 mm shall be flat and 20 mm shall be tapered in 45 degree angle on both side forming styles and 5 mm thick, 95 mm wide PVC sheet out of which 75mm shall be	
adhesive etc. complete shall have a coat of steel primers of approved make and manufacture. M.S. frame covered with 5 mm thick heat moulded PVC 'C' channel of size 30 mm thickness, 70 mm width out of which 50 mm shall be flat and 20 mm shall be tapered in 45 degree angle on both side forming styles and 5 mm thick, 95 mm wide PVC sheet out of which 75mm shall be	
coat of steel primers of approved make and manufacture. M.S. frame covered with 5 mm thick heat moulded PVC 'C' channel of size 30 mm thickness, 70 mm width out of which 50 mm shall be flat and 20 mm shall be tapered in 45 degree angle on both side forming styles and 5 mm thick, 95 mm wide PVC sheet out of which 75mm shall be	
make and manufacture. M.S. frame covered with 5 mm thick heat moulded PVC 'C' channel of size 30 mm thickness, 70 mm width out of which 50 mm shall be flat and 20 mm shall be tapered in 45 degree angle on both side forming styles and 5 mm thick, 95 mm wide PVC sheet out of which 75mm shall be	
covered with 5 mm thick heat moulded PVC 'C' channel of size 30 mm thickness, 70 mm width out of which 50 mm shall be flat and 20 mm shall be tapered in 45 degree angle on both side forming styles and 5 mm thick, 95 mm wide PVC sheet out of which 75mm shall be	
moulded PVC 'C' channel of size 30 mm thickness, 70 mm width out of which 50 mm shall be flat and 20 mm shall be tapered in 45 degree angle on both side forming styles and 5 mm thick, 95 mm wide PVC sheet out of which 75mm shall be	
mm thickness, 70 mm width out of which 50 mm shall be flat and 20 mm shall be tapered in 45 degree angle on both side forming styles and 5 mm thick, 95 mm wide PVC sheet out of which 75mm shall be	
which 50 mm shall be flat and 20 mm shall be tapered in 45 degree angle on both side forming styles and 5 mm thick, 95 mm wide PVC sheet out of which 75mm shall be	
mm shall be tapered in 45 degree angle on both side forming styles and 5 mm thick, 95 mm wide PVC sheet out of which 75mm shall be	
angle on both side forming styles and 5 mm thick, 95 mm wide PVC sheet out of which 75mm shall be	
and 5 mm thick, 95 mm wide PVC sheet out of which 75mm shall be	
sheet out of which 75mm shall be	
45 degree on the inner side to form	
7 top and bottom rail and 115 mm 3.60 sqm -do-	
wide PVC sheet out of which 75	
mm shall be flat and 20 mm shall be	
tapered on both sides to form lock	
rail. Top, bottom and lock rails shall	
be provided both side of the panel.	
10 mm (5 mm x 2) thick, 20 mm	
wide cross PVC sheet be provided	
as gap insert for top rail & bottom	
rail, panelling of 5 mm thick both	
side PVC sheet to be fitted in the	
M.S. frame welded/ sealed to the	
styles & rails with 7 mm (5 mm+2	
mm) thick x 15 mm wide PVC sheet	
beading on inner side, and joined	
together with solvent cement	
adhesive. An additional 5 mm thick	
PVC strip of 20 mm width is to be	
stuck on the interior side of the 'C'	
Channel using PVC solvent	
adhesive etc. complete as per	
direction of Engineer-in-charge,	
manufacturer's specification &	
drawing.30 mm thick plain PVC	
door shutters	
Quarter-E-3 and E-7	
Providing wood work in frames of	
8 false ceiling, partitions etc. sawn	
and fixed in position with necessary	

	stainless steel screws etc. Sal wood	0.421	Cum			
9	Quarter-E-3 and E-7 Providing and fixing insulating board ceiling of approved quality with necessary nails etc. complete (frame work to be paid separately)6: White face insulating board 12 mm thick Quarter-E-3 and E-7	66.120	Sqm	-do-		
10	Providing and fixing wash basin with C.I. brackets, 15 mm C.P. brass pillar taps, 32 mm C.P. brass waste of standard pattern, including painting of fittings and brackets, cutting and making good the walls wherever require: White Vitreous China Angle back wash basin size 400 x 400 mm with single 15 mm C.P. brass pillar tap Quarter-E-3 and E-7	2	Nos	-do-		
11	C.P. Brass bibcock 15 mm Quarter-E-3 and E-7	2	Nos	-do-		
			Tot			
	Total	(Grand	Total		

Total amount in words

PerformanceSchedule:30 days from issue of work order.

Specifications/SpecialConditionsofContract: work should be performed as per CPWD manual/specification & direction of Engineer-in-charge.

Item/TenderSpecificConditionsofthisTender:

I/we engage to performance the works to your office and comply the following:

- 1. Tenderscheduleandtechnicalspecificationindicated.
- 2. Item/tenderspecificconditionsforthistender.
- 3. Termsandconditionsprintedoverleaf.
- 4. General conditions of contract signed by me at the time of supplier registration (for registered suppliers).
- 5. I/we confirm that set off for the GST, etc. Paid on the inputs have been taken into consideration in the above quoted price and further agree to pass on such additional duties as sets offs as may become available infuture under GST, etc.
- 6. This offer is valid for 90 (ninety) days from the date of opening of the quotations.
- 7. ThatwehavenotbeendebarredbyanyGovernment/Undertaking.
- 8. Thattheratesquotedarenothigherthantheratesquotedforsameitemtoany Government / Undertaking.
- 9. That the bid submitted by us is properly sealed and prepared so as to prevent any subsequent alteration andreplacement.

Signature & SealPlace&Date:	Name of Authorized Signatory:	
Address:	Tel. No./ Fax. No./ MobileNo. EmailId:	

TERMSAND CONDITIONS OFLIMITED TENDER

- i) The quotation must be in the form furnished by procuring entity and should be free from corrections/erasures. In case there is any unavoidable correction it should be properly attested. If not the quotation will not be considered. Quotation written in pencil will not be considered.
- ii) Quotation will be opened on due date at 3.30pm at the indicated venue in presence of the entities or their representatives who may wish to be present.
- iii) The Government of India reserves the right to accept the offer by individual items andreject any or all tenders without assigning any reason thereof and does not bind itself to accept lowest quotations.
- Participation in this tender is by invitation only and is limited to the reputed entity involved in similar type of work. Unsolicited offers are liable to be ignored. However, relevant entity who desire to participate in such tenders in future may bring it to the notice of procuring entity and apply for registration as per procedure.
- v) Complete details and specification if any must accompany the quotation. If you have got any counter offer assuitable to the material required by us, the same may be shown separately.
- vi) The Government of India reserves the right to modify the work specified in this enquiry.
- vii) The prices quoted should be firm till the works are completed. Please quote the rates inwordsandfigures. Price quoted should be net and valid for a minimum period of three months from the date of opening of the quotation.
- viii) Payment of GST is primarily the responsibility of the seller and will not be paid unlessthe percentage value is clearly mentioned in the quotations. If no indication regarding GST is recorded in the quotation, the GST will be considered as included.
- ix) The performance period required for completion of work should be invariably specified in thequotation.
- In case your quotation is accepted and order is placed on you, the work completion against theorder should be made within the period stipulated in the order. The Government of Indi a reserves the right to recover any loss sustained due to delayed completion of work by way ofpenalty. Failure to performance of work within the stipulated period shall entitle Procuring Entity for the imposition of penalty without as signing any reasons@ 0.5% of the total value of the item covered in order as penalty per day subject to a maximum of 5% (five percent) unless extension is obtained in writing from the office on valid groundbeforeexpiryof performance period.
- xi) The quotationers may visit the site before submitting quotation of the above work.
- xii) Dispute clause: Any dispute relating to the enquiry shall be subject to the jurisdiction of the courtat____(name of the place of tender invitation)only.
- Our normal payment will be made to the contractor on satisfactory completion of work on submission of prereceipted bill in triplicate with mandate form, payment will be made by through e-payment.

Copy to:

- 1. The Accounts Branch, NEID-II, CWC, Aizawl.
- 2. Notice Board.