



84/93-96, प्रताप नगर, सांगानेर, जयपुर -302033
फोन: 0141-2790065, ई-मेल: chambalcwc@yahoo.co.in

पत्र क्रमांक: चमज/ के.ज.आ./मु.-1/2023/323-27

दिनांक: 31.01.2024

कोटेशन आमंत्रण सूचना (NOTICE INVITING QUOTATION)

भारत के राष्ट्रपति की ओर से अधिशाषी अभियंता, चम्बल मंडल, जयपुर द्वारा अधिकृत तथा योग्य बोलीदाताओं से “निचली चम्बल उपमंडल, जयपुर के अधीनस्थ मंडरायल स्थल पर मरम्मत एवं नवीनीकरण का कार्य हेतु कोटेशन” लिखा हुआ मुहरबंद कोटेशन आमंत्रित किये जाते हैं।

Sealed quotation super scribed as “Quotation for Repair & Renovation of Mandrayal office under Lower Chambal Sub-division, CWC, Jaipur” are invited for and on behalf of the President of India by the Executive Engineer, Chambal Division, CWC, Jaipur from the authorized and eligible bidders.

नियम एवं शर्तें (Terms & Conditions)

- हस्ताक्षरित व मुहरबंद कोटेशन अधिशाषी अभियंता, चम्बल मंडल, केन्द्रीय जल आयोग, जयपुर के कार्यालय में दिनांक 07.02.2024 पूर्वान्ह 11:00 बजे तक या उससे पूर्व प्राप्त हो जानी चाहिए, जो उसी दिन अर्थात् 07.02.2024 दोपहर 12:00 बजे अधोहस्ताक्षरी तथा बोली लगाने वाले या उसके प्रतिनिधि जो उपस्थित रहना चाहे की उपस्थिति में खोली जाएगी।
The sealed & signed quotation shall reach to the office of Executive Engineer, Chambal Division, CWC, Jaipur on or before 07.02.2024 upto 11:00 A.M. and will be opened on the same day i.e. 07.02.2024 at 12:00 P.M. in the presence of undersigned and bidders or their representative who may likely to be present at the time of opening of quotations.
- मुहरबंद कोटेशन के साथ रुपये 7936/- की ईएमडी केवल डिमांड ड्राफ्ट/एफडीआर के रूप में अधिशाषी अभियंता, चम्बल मंडल, के.ज.आ., जयपुर के पक्ष में संलग्न करना अनिवार्य है। बिना ईएमडी के प्राप्त कोटेशन को खारिज कर दिया जाएगा। MSE & Startup को ईएमडी जमा करने की छूट दी गई है।
The EMD of Rs. 7936/- in the form of only Demand Draft/FDR in favor of Executive Engineer, Chambal Division, CWC, Jaipur should be enclosed with sealed quotation. Quotations received without EMD will be summarily rejected. MSE & Startup are exempted from payment of EMD.
- कोटेशन नोटिस (सभी अनुलग्नकों और मूल्य बोली सहित) के सभी पृष्ठों पर सील और हस्ताक्षर करना अनिवार्य है। बिना seal and sign (सभी पृष्ठों पर) के प्राप्त कोटेशन को खारिज कर दिया जाएगा।
The quotationer must seal and sign at all pages of the quotation notice including all annexures and price bid failing which the quotation will summarily rejected.
- अंतिम तिथि व समय के पश्चात प्राप्त कोटेशन स्वीकार नहीं करी जाएगी और गैर-उत्तरदायी मानी जाएगी।

Quotation received after the last submission date & Time will not be accepted and will be treated as non-responsive.

5. कार्य करने की अवधि कार्यदिश जारी होने के बाद से 30 दिन की रहेगी।
Work shall be carried within 30 days after issue of work order.
6. कोटेशन में दर्शायी गयी राशि सभी प्रकार के टैक्स (GST etc.) के साथ होनी चाहिए तथा Annexure-1 में निर्धारित जगह पर ही राशि को दर्शाये।
Rates shall be quoted including of all Taxes (GST etc.) and rates should be mentioned in Annexure-1 at their shown place only.
7. दरें अंकों और शब्दों दोनों में उद्धृत की जानी चाहिए और बिना किसी अधिलेखन के सुपाठ्य रूप से लिखी जानी चाहिए। किसी भी सुधार के मामले में, इसे बोलीदाता द्वारा पूर्ण हस्ताक्षर के साथ सत्यापित किया जाना चाहिए। अंकों और शब्दों में दरों के बीच कोई अंतर होने पर शब्दों में लिखी दरों को सही माना जाएगा।
The rates should be quoted both in figures and words and legibly written without any over-writings. In case of any correction, the same must be attested by the bidder with a full signature. In case of any discrepancy between the rates in figures and that in words, the rate in words will be accepted as correct.
8. इस कार्य हेतु इस्तेमाल में लिया गया सामान अच्छी गुणवत्ता का एवं दिए गये विशेष विवरण के अनुसार तथा त्रुटि रहित होना चाहिए।
The material used for this work must be of standard quality and as per specifications and free from all the defects.
9. कोटेशन में दर्शायी दरे, कोटेशन खुलने के दिन से कम से कम 60 दिन तक वैध होनी चाहिए।
Rates quoted should be valid at least for 60 days from date of opening.
10. उक्त कार्य मंडरायल स्थल (जिला-करौली, राजस्थान) पर होना हैं, जिनका दरें डालने से पूर्व निरीक्षण किया जा सकता हैं।
The above work is to be done at site Mandrayal (Dist.-Karauli, Rajasthan), which (Place) can be inspected before quoting the rates.
11. कोटेशनर के पास PAN/GST No. होना चाहिए (प्रतिलिपि संलग्न की जाए)। बिना PAN तथा GST No. प्रतिलिपि के प्राप्त कोटेशन को खारिज कर दिया जाएगा।
Quotationer must have PAN/GST No. (Copy to be enclosed). Quotations received without copy of PAN & GST No. will be summarily rejected.
12. अधोहस्ताक्षरी किसी एक या सभी कोटेशन को बिना कारण बताये स्वीकार या अस्वीकार करने का अधिकार सुरक्षित रखता हैं।
Undersigned reserves the right to accept or reject any or all the quotations without assigning any reason thereof.
13. कार्य की मात्रा कार्यदिश के समय या कार्य करने के दौरान बढ़ाई या कम की जा सकती हैं।
The quantity of work may be increased or decreased at the time of work order or during the time of execution.
14. कोटेशन स्वीकृत होने पर, फर्म/एजेंसी को किसी भी वाणिज्यिक बैंक से Account Payee D.D/ Fixed Deposit Receipt/ Banker's cheque or Bank Guaranty के रूप में निविदा राशि के 3% की दर से परफॉर्मेंस गारंटी

जमा करनी होगी जो की अधिशाषी अभियंता, चंबल मण्डल, के.ज.आ., जयपुर को देय होगी। परफॉरमेंस गारंटी कार्य समाप्त होने के 60 दिन बाद तक वैध होनी चाहिए।

On acceptance of the quotation, the Firm/Agency shall have to submit performance Guarantee @ 3% of the tendered amount in the form of an Account Payee D.D/ Fixed Deposit Receipt/ Banker's cheque or Bank Guaranty from any of the commercial bank in favour of Executive Engineer, Chambal Division, CWC, Jaipur payable at Jaipur. This should remain valid for a period of sixty days beyond the date of completion of work.

15. कार्य के संतोषजनक पूर्ण होने के बाद सम्पूर्ण भुगतान में से आवश्यक कटौती (2.5 % Security Deposit, 2 % GST, 2% TDS, 1% Labour Cess) पश्चात भुगतान को ECS/RTGS के द्वारा किया जायेगा। अमानत राशी (Security Deposit) का भुगतान कार्य समाप्त होने के 06 माह के पश्चात किया जायेगा।

Payment will be made through ECS/RTGS, only after satisfactory completion of work and deduction of necessary Deductions (2.5% Security Deposit, 2% GST, 2% TDS, 1% Labour Cess). Security Deposit amount will be given after 06 months of completion of work.

Sd/-
अधिशाषी अभियंता
चम्बल मंडल, के.ज.आ., जयपुर

प्रतिलिपि सूचनार्थ:

1. सहायक लेखाधिकारी, लेखा शाखा, चम्बल मंडल, जयपुर।
2. उप मंडलीय अभियंता, नि.च.उ.मं., जयपुर।
3. सहायक, पत्राचार शाखा, चम्बल मंडल, जयपुर।
4. सूचना पट्ट, चम्बल मंडल, जयपुर।
5. विभागीय वेबसाइट।

Schedule of Quantity

Name of work: Repair & Renovation of Mandrayal office under Lower Chambal Sub-division, CWC, Jaipur

| Item No. | Sub-head and items of work | Qty. | Unit | Rate in Rs. (Incl. GST) | Amount in Rs. |
|-----------------|--|-------------|-------------|--------------------------------|----------------------|
| 1 | Removing dry or oil bound distemper, water proofing cement paint and the like by scrapping, sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete. | 326.91 | Sqm | | |
| 2 | Taking out existing wooden door shutter, repair by cutting, painting etc. and refixing of repaired door shutters to existing door frames, including replacement of hinges with screws, etc. as required, all complete as per the direction of the Engineer-in-charge. | 3.00 | Each | | |
| 3 | Dismantling stone slab flooring laid in cement mortar including stacking of serviceable material and disposal of unserviceable material within 50m lead | 42.57 | sqm. | | |
| 4 | 12 mm cement plaster of mix: 1:4 (1 cement: 4 fine sand) | 326.91 | sqm. | | |
| 5 | Providing and applying white cement-based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete. | 117.92 | sqm. | | |
| 6 | Distempering with oil bound washable distemper of approved brand and manufacture to give an even shade: New work (two or more coats) over and including water thinnable priming coat with cement primer | 326.91 | sqm. | | |
| 7 | Providing and laying vitrified floor tiles in different sizes (thickness to be specified by the manufacturer) with water absorption less than 0.08% and confirming to IS:15622, of approved make, in all colors and shades, laid on 20 mm thick cement mortar 1:4 (1 cement : 4 coarse sand) jointing with grey cement slurry @ 3.3 kg/sqm including grouting the joints with white cement and matching pigments etc complete Size of tile 600*600 mm | 36.63 | sqm. | | |
| 8 | Cement concrete flooring 1:2:4 (1 cement: 2 coarse sand: 4 graded stone aggregate) finished with a floating coat of neat cement, including cement slurry, but excluding the cost of nosing of steps etc. complete. 11.3.1 40 mm thick with 20 mm nominal size stone aggregate | 52.74 | sqm. | | |

| | | | | | |
|----|--|-------|-------|--|--|
| 9 | Providing and laying in position cement concrete of 1:4:8 (1 cement: 4 sand (zone III) derived from natural sources: 8 graded stone aggregate 40 mm nominal size derived from natural sources) excluding the cost of centering and shuttering - All work up to plinth level. | 1.40 | Cum | | |
| 10 | Providing and laying APP (Atactic Polypropylene Polymer) modified prefabricated five-layer, 3 mm thick water proofing membrane, black finished reinforced with glass fibre matt consisting of a coat of bitumen primer for bitumen membrane @ 0.40 litre/sqm by the same membrane manufactured of density at 25°C, 0.87 - 0.89 kg/litre and viscosity 70 - 160 cps. Over the primer coat the layer of membrane shall be laid using butane torch and sealing all joints etc., and preparing the surface complete. The vital physical and chemical parameters of the membrane shall be as under: Joint strength in longitudinal and transverse direction at 23°C as 350/300 N/5 cm. Tear strength in longitudinal and transverse direction as 60/80N. Softening point of membrane not less than 150°C. Cold flexibility shall be upto -2°C when tested in accordance with ASTM, D - 5147. The laying of membrane shall be got done through the authorised applicator of the manufacturer of membrane: 14.90.1 3 mm thick | 78.94 | sqm. | | |
| 11 | Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade: One or more coats on old work | 26.59 | sqm. | | |
| 12 | Supplying and fixing PVC batten/ angle holder including connections etc. as required. | 12.00 | Each | | |
| 13 | Supplying and fixing following modular switch/ socket on the existing modular plate & switch box including connection but excluding modular plate etc. as required. | | | | |
| | 5/6 A switch | 11.00 | Each | | |
| | 15/16 A switch | 5.00 | Each | | |
| | 3 pin 5/6 A socket outlet | 8.00 | Each | | |
| | 6 pin 15/16 A socket outlet | 5.00 | Each | | |
| 14 | Supplying and fixing two module stepped type electronic fan regulator on the existing modular plate switch box including connections but excluding modular plate etc. as required. | 4.00 | Each | | |
| 15 | Wiring for light/ power plug with 2X4 sq. mm FRLS PVC insulated copper conductor single core cable in surface/ recessed medium class PVC conduit along with 1 No. 4 sq. mm FRLS PVC insulated copper conductor single core cable for loop earthing as required. | 30.00 | Meter | | |
| 16 | Supplying and fixing following size/ modules, GI box along with modular base & cover plate for modular switches in recess etc. as required. | | | | |
| | 1 or 2 Module (75mmX75mm) | 8.00 | Each | | |

| | | | | | |
|-----------------------------------|--|-------|-------|--|--|
| | 4 Module (125mmX75mm) | 4.00 | Each | | |
| | 6 Module (200mmX75mm) | 4.00 | Each | | |
| 17 | Supplying and fixing of 25 mm of medium class PVC conduit along with accessories in surface/recess including cutting the wall and making good the same in case of recessed conduit as required. | 40.00 | Meter | | |
| 18 | Supplying and fixing following way, single pole and neutral, sheet steel, MCB distribution board, 240 V, on surface/ recess, complete with tinned copper bus bar, neutral bus bar, earth bar, din bar, interconnections, powder painted including earthing etc. as required. (But without MCB/RCCB/ Isolator): 12-way, Double door | 1.00 | Each | | |
| 19 | Supplying and fixing 5 A to 32 A rating, 240/415 V, 10 kA, "C" curve, miniature circuit breaker suitable for inductive load of Single pole in the existing MCB DB complete with connections, testing and commissioning etc. as required. | 6.00 | Each | | |
| 20 | Providing and fixing on wall face unplasticized Rigid PVC rain water pipes conforming to IS: 13592 Type A, including jointing with seal ring conforming to IS: 5382, leaving 10 mm gap for thermal expansion, (i) Single socketed pipes of 110 mm diameter | 18.00 | Meter | | |
| 21 | Providing and fixing on wall face unplasticized - PVC molded fittings/ accessories for unplasticized Rigid PVC rain water pipes conforming to IS: 13592 Type A, including jointing with seal ring conforming to IS: 5382, leaving 10 mm gap for thermal expansion. Bend 87.5°, 110 mm bend | 6.00 | Each | | |
| Grand Total in figures Rs. | | | | | |
| Grand Total in Words | | | | | |

Note: Quotations received without mentioning Grand Total in Figures & words both will be summarily rejected.

Terms & conditions: - As per NIQ
Issuing Authority

Sd/-
Executive Engineer
Chambal Division

Signature of Contractor
Seal
Address